


# COLOR - 8201

## TECHNICAL SPECIFICATIONS

- COMPRESSIVE STRENGTH (DRY): ASTM C170-17 234 Mpa
- DENSITY: ASTM C97-18 2400 kg/m<sup>3</sup>
- WATER ABSORPTION: ASTM C97-18 0.03%
- THICKNESS: Standard 2cm or 3cm. Custom Available
- ABRASION RESISTANCE: ASTM C241-15 48
- MOHS HARDNESS: EN 15771 Averages 6
- STAIN RESISTANCE: ANSI Z124.6-07 Pass
- CHEMICAL RESISTANCE: ASTM C650 Not Affected
- FLEXURAL STRENGTH (DRY): ASTM C880-14 37.2 Mpa
- THERMAL SHOCK RESISTANCE: ASTM-C484 No Defect
- MODULUS OF RUPTURE: ASTM C99 39
- FINISH: Polished (level 6000 available)
- EDGE: As Specified



\*SAMPLE IMAGE FOR REFERENCE ONLY\*

## APPLICATION

- VANITY TOPS
- KITCHEN TOPS
- WINDOW SILL
- DESK TOPS
- DRESSER TOPS
- THRESHOLD
- WALL CLADDING

## NOTES

- PATENT PENDING
- 0% ACRYLIC SOLID SURFACE
- FOR MORE INFORMATION ON WHAT ULTRACERA® IS, AND WHAT IT IS NOT: PLEASE VISIT [ULTRACERATOPS.COM](http://ULTRACERATOPS.COM)

\* Specifications and data listed herein are subject to change without notice due to constant product and engineering improvements